

# TECHNICAL DATASHEET

## CONTOUR 100 - SELF CONTAINED BREATHING APPARATUS



### DESCRIPTION

The Scott Contour 100 is an open circuit, self-contained, compressed air breathing apparatus. It consists of a back plate, unpadded carrying harness and pneumatic system, containing a cylinder connector, reducer, pressure gauge, whistle and demand valve.

The Contour 100 can be configured in a number of different ways with various size single cylinders. There are also a range of attachments available including Airline (AC), Split Demand Valve Coupling (SDC), Rescue Second Man (RSM) and Decontamination (DC).

The Contour 100 is used in conjunction with a range of composite or steel cylinders and the choice of Vision 3, Panaseal, Panavisor or Promask PP facemask.

### APPLICATIONS

The Contour 100 is specifically designed as a Industrial Fire Fighting SCBA, but is also suitable for providing respiratory protection in any IDLH environment.

### APPROVALS

CE marked in accordance with EN137:1998 Type I

CE marked in accordance with EN139 - sets fitted with CEN airline attachments

AS1716

# TECHNICAL DATASHEET

## MATERIALS

Pressure Reducing Valve	Nickel Plated Brass
Rust Tube (Sabre Cyls)	Brass
Reducing Valve Seat	Polyamide (Nylon)
O-Rings	Nitrile, Silicone, EPDM
Reducing Valve Springs	Stainless Steel
HP Pressure Gauge	Stainless Steel, Polycarbonate Lens
HP Pressure Gauge Cover	Neoprene
MP Air Supply Hose Fittings	Nickel Plated Brass
Facemask	Neoprene, Silicone or Procomp
Facemask Visor	Polycarbonate
MP Air Supply Hose	Chlorinated Polyethylene, fabric braid reinforcement, Nitrile liner
HP Air Hose	PTCFE liner, stainless steel braiding, Estane sleeve
Valve Handwheel (Sabre Cyls)	Glass filled Polyamide
Harness	Intrinsically flame retardant 50% Kevlar blend
Backplate	Glass & Carbon filled Nylon composite
Backpad	Flame retardant polyamide and closed cell Polyethylene foam
Cylinder Band	100% Kevlar
Strap Buckles	Stainless Steel, Brass
Cylinder	Steel or Composite
Cylinder Valve	Nickel Plated Brass
Demand Valve Casing	Glass filled Polyacetal and Polyamide

## MAINTENANCE/CLEANING/SERVICING

N.B. - Cleaning should only be carried out as specified in the user instructions. Maintenance and servicing must only be performed by trained personnel following the procedures in the Service and Maintenance manual.

# TECHNICAL DATASHEET

## TECHNICAL SPECIFICATIONS

### Tempest Demand Valve

Compact positive pressure demand valve featuring servo-assisted, tilting diaphragm mechanism with low inspiratory resistance and responsive dynamic performance, automatic first breath actuation and hands free bypass facility. Components injection moulded from Polyamide with rubber seals and diaphragms.

First breath activation	-20 to -30 mbar
Peak flow performance	In excess of 500 litres/minute
Bypass flow	150 litres/minute nominal
Static positive pressure	1.0 – 4.0 mbar

### Reducing Valve

First stage pressure reducing valve featuring non-adjustable, spring loaded piston mechanism and outlet supply protected by pressure relief valve. Valve body and cap machined from nickel-plated brass with stainless steel spring and hose retainer U-clips.

Outlet Pressure	
200 bar inlet	5.5 to 9.5 bar
300 bar inlet	6.0 to 11.0 bar
Pressure relief valve protected	Approx. 13.5 bar
Flow restrictor to gauge supply hose	<25 litres minute

### Pressure Indicator & Warning Whistle

Bourdon tube type dial indicator	
Heat and impact resistant Polycarbonate lens	
Safety blow-out vent in rear of gauge	
Accuracy	+/- 10 bar between 40-300 bar

### Hoses

#### *Stainless Steel swivel hose fittings*

#### *Medium Pressure Hose*

Maximum working pressure	16 bar
Minimum burst pressure	80 bar

#### *High Pressure hose*

Maximum working pressure	450 bar
Minimum burst pressure	800 bar

### Weight/ Dimensions

Single configuration (less cylinder)	2.3kg
Single configuration & facemask (less cylinder)	3.0kg
Length	600mm
Width	278mm
Depth (with 6.0 litre 200 bar cylinder)	200mm