PREMIUNA A WRAP-AROUND PROTECTIVE FRAME

Bollé Safety offers a simple and flexible system, based on a unique pricing. The RX range is composed of a wide range of frames that can be glazed with 3 types of prescription lenses (single vision, bifocal, progressive) and 3 different lens materials (polycarbonate, CR39 or toughened glass).





26 g

SUPPLIED WITH

Hard case, microfibre cloth, cord FRAME

LENS MATERIAL AVAILABLE

- CR39
 - Polycarbonate



"Plastic" Acetat



- **+** UPPER PROTECTION
- **H** LOWER PROTECTION



PRENIUX A WRAP-AROUND PROTECTIVE FRAME

MODEL	VERSIONS	REFERENCES	SIZE	FRAME MARKING	TEMPLE LENGTH
PREMIUM	Acetat / Clear blue Grey	PREN	60/20	☑ EN166 F C €	140 mm

LENS MARKING

Lens available in clear, 3 shades of gray and 3 shades of smoke.

Polycarbonate lens:

F. Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s Maximum protection for glasses.

CR39 lens:

S. Extra strong, resists a 22 mm 43 g ball falling 1.30 m at 5,1 m/s.

FRAME MARKING

EN 166 : guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

- F. Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s Maximum protection for glasses.
- C∈ European standard ☆ Manufacturer name

Bollé safety product approval certificates to CE standards will be sent on request.

CLEANING AND STORAGE

CLEANING : The lenses should be cleaned regularly. Bollé Safety recommends only using the B-clean lens cleaning system.

MAINTENANCE : Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

STORAGE : All products must be stored in a dry and clean environment.

CHARACTERISTICS			
LENS	CR39, Polycarbonate		
TYPES OF CORRECTIONS AVAILABLE	Single vision - Bifocal - Progressive		
FRAME	Acetat / Clear blue grey		
STRAP	Non applicable		
FOAM	Non applicable		



Europe Bollé Safety 95 rue Louis Guérin 69100 Villeurbanne - France Tél. : 00 33 (0) 4 78 85 23 64 Fax : 00 33 (0) 4 78 85 28 56 contact@bolle-safety.com

U.K. Bollé Safety Unit C83 - Barwell Business Park Leatherhead Road - Chessington Surrey - KT9 2NY Tél. : 00 44 (0)208 391 4700 Fax : 00 44 (0)208 391 4733 e-mail : sales@bolle-safety.co.uk

مارخ

14/01/2014

bolle-safety.com

Maximum sphere power +4/-4 Maximum cylinder compared with sphere : +/-3.

STANDARD ASSEMBLY RESTRICTIONS:

CORRECTED BASE:

Corrected base : 6

PACKAGING AND EAN13 CODE		
	PREN	
Per piece	3660740001889	