

ULTRA-LOK® SELF-RETRACTING LIFELINE WITH RESCUE

FALL ARREST BLOCKS

1 OVERVIEW

ULTRA-LOK® SRL's come with a durable glass-filled polyurethane housing, a 3/16" wire rope lifeline and aluminium side plates for maximum durability and minimum weight. For added security, ULTRA-LOK® systems have an anti-ratcheting twin disc brake system with an audio indicator to let you know it is functioning properly.

This model is the world's first dual-mode self-retracting lifeline fall arrest and rescue device. It operates in either Fall Arrest Mode or Automatic Rescue Mode.

FALL ARREST MODE:

After setting the fall arrest mode, should a fall occur the following will happen: A speed sensing brake stops the fall, reduces forces imposed on the user to safe levels of 6kN or less and allows for assisted rescue to take place.

AUTOMATIC RESCUE MODE:

After setting the automatic rescue mode, the device will operate like a descender, should a fall occur, the following will happen: A speed sensing brake slows the fall, then instantly a centrifugal brake activates, lowering the user at a controlled speed to the next level or ground.



2 FEATURES

- ❑ Exclusive Design Provides Both Fall Arrest with Assisted Rescue Capabilities and Automatic Self Rescue for Ultimate Versatility
- ❑ Fall Arrest Mode Stops Falls within Few Decimetres and Limits the Forces to 6kn for Less for Added Safety
- ❑ Assisted Rescue Procedures Can Then Be Implemented either At the Mode Selector or Remotely With a First-Man-Up™ Pole
- ❑ Self Rescue Mode Automatically Lowers the User to the Next Level after a fall
- ❑ Lightweight And Long Lasting Durable Reinforced Plastic Housing. Incorporates a Built-In Carrying Handle for Easy Transportation
- ❑ 15M Cable Extends and Retracts Automatically Enabling the User to Move around the Work Area Protected
- ❑ I-Safe™ Intelligent Safety System Is Built-Into Every Unit to Track Inspections, Control Inventory and Manage Information
- ❑ Designed To Meet Worldwide Standards Including CE EN360 and EN341

3 PRODUCT SPECIFICATIONS

RATED CAPACITY: 34kg to 141kg

MAXIMUM ARRESTING FORCE: 6kN

DESCENT SPEED: 1m/s

LENGTH OF CABLE: 15m

SIZE:

- ❑ 20cm Wide
- ❑ 29cm Long
- ❑ 9cm Thick

WEIGHT: 8.5kg

HOUSING MATERIAL: 2 Pieces, Thermoplastic Composite

CABLE MATERIAL: 5mm, 7x19 Galvanised Cable

SNAP HOOK: Zinc Plated Alloy Steel, Self Locking and Swivelling, 22.2kN Tensile Strength

STANDARDS: Meets CE EN 360 and EN341